



Y-PIPE

PART # 17470 & 17478
CAMARO, FIREBIRD & TRANS AM
1982-1991 5.0 - 5.7L

17470 - Uses Gasket

17478 - Ball and Socket

FOR USE WITH
HEDMAN #61478, 66471, 66474, 66479, 68470,
68471, 68474, 68476, 68478 & 68479

INSTALLATION INSTRUCTIONS

1. Using flanges, gaskets, bolts and nuts provided, install main section of y-pipe to right side of hedder. Do not tighten.
2. Insert short pipe into main section of y-pipe and bolt to the left side hedder.
3. Align y-pipe to clear oil pan and sub-frame and tighten collector bolts.
4. For 3" inlet converters use adapter and 2½" u-clamp.
5. Note: We recommend using a muffler seal or welding y-pipe at the slip connection. **USING A U-CLAMP COULD DAMAGE OIL PAN!**
6. Start the engine and take for a test drive listening for any new or unusual sounds. Allow engine and exhaust to reach operating temperature. After test drive, allow system to cool and re-tighten all bolts and clamps.

Due to the use of many different converters, it may require cutting and welding to adapt stock converter.

ENJOY THE ADDED POWER AND PERFORMANCE OF YOUR NEW SYSTEM.

12438 Putnam Street • Whittier, CA 90602 • tel (562) 921-0404 • fax (562) 921-7515
website: www.hedman.com • email: techsupport@hedman.com